**20**: 06724-238511



## BALIKUDA WOMEN'S DEGREE COLLEGE

AT/PO.: BALIKUDA, DIST: JAGATSINGHPUR, PIN: 754108

(R. D. of Edn. Order No. :- 7640 (3), Dt. 12-05-10)

E-mail ID: balikuda.womens.drcollege@gmail.com

www.: balikudawomensdrcollege.org

#### Quotation Call Notice

| •    |   | 1 | 11 |     | 05. | 2415 |
|------|---|---|----|-----|-----|------|
| Date | · | 4 | М. | ٠., |     | 2425 |

Sealed Quotations are invited from the intending registered firm/Supply Agency/Authorised dealer for procurement-of IT items for upgradation of IT infrastructure as per the specifications mentioned at Annexure A for Balikuda Women's Degree College in the district of Jagatsinghpur.

Details of quotations along with terms & conditions are available at this district website i.e. jagatsinghpur.odisha.Gov.in. & college website i.e. balikudawomensdrcollege.org. The terms & conditions along with declaration must be signed by the quotationer as of acceptance of terms & conditions and be submitted along with the quotation.

The quotations complete in all respect must be submitted in a sealed cover through registered/Speed post only to the principal, Balikuda Women's Degree College, At /Po- Balikuda, Dist - Jagatsinghpur, Pin- 754108 on or before 09.06.2025 by 12 noon.

The quotations shall be opened on 11.06.2025 at 11.00 A.M before the purchase Committee in presence of quotationer (s) or his/her authorized representatives only.

The quotations received beyond the scheduled date & time will be summarily rejected.

The Committee reserves the right to accept / reject any of all quotations without assigning any reason thereof.

Balikuda Women's Degree College Memo No. 745 (1) Dt 24.05.26 Principal-I/C BalikudaWomensDegreeCollege Copy forwarded to the DIO, NIC, jagatsinghpur and is requested to upload to the notice in the official website of jagatsinghpur district for wide publicity. Balikuda Women's Degree College 745(11) Principal-I/C BalikudaWomensDegreeCollege

Copy forwarded to the Regional Director, RDE, Bhubaneswar for his kind information & necessary action.

> Balikuda Women's Degree College Principal-I/C BalikudaWomensDegreeCollege

Balikada, Jagatsinghpur

## TERMS AND CONDITIONS FOR QUOTATIONERS FOR SUPPLY OF IT ITEMS

- The Intending registered firm/Supply agency/authorized Dealer must have to attach the copy of their valid GST,PAN and IT return certificate at the time of submission of quotation and OEM(ISO 9001,14001,ISO 2001,ISO 27001)Bid specific authorization, Microsoft Windows, Energy Star 8.0 certificate copy, BIS,BEE,EPEAT, UL,ROHS Certificate of products at the time of Participation of the BID
- The entry should not be black listed by the State/Central Govt. or by any other Organization and to submit a declaration to that effect as attached.
- 3. All rats quoted should be inclusive of GST.
- 4. Any defective/damage materials must be replaced within 3 days of reporting.
- The quotations as per specification given at Annexure-A must be filled correctly & legible without any overwriting.
- 6. The successful bidder will have to supply the items within 3 days from the date of purchase order.
- 7. Labour Cost and transportation will be borne by the firm.
- 8. The quotation documents will be submitted in a sealed envelope superscribing "SUPPLY OF IT ITEMS" through registered/speed post to the Principal, Balikuda Women's Degree college, At/Po-Balikuda, Dist-Jagatsinghpur, PIN-754108 within the stipulated date & time.
- 9. The detailed specification of IT items is attached in Annexure-A
- The committee reserves the right to accept/reject any or all quotations without assigning any reason thereof.
- 11. The authority will not be responsible for missing or delay of any quotation in transit.
- 12. If any dispute arises, the matter shall be reported to the Chairperson of Committee for settlement of dispute.

Balikuda womens Degree college Balikuda,Jagatsinghpur

Principal-I/C

BallkudaWomenaDegreeCollege P to Jack Singhour

#### Declaration

I/We hereby certify that, the terms and conditions along with specification of items given in the quotation call notice have been read carefully and are acceptable to me/us.

Further, I/We certify that my/our organization has not been blacklisted by any State/ Central Govt. or any other organization.

Place:

Date:

Signature with seal of Authorised Signatory

### LIST OF ITEMS TO BE PURCHASED

| SINo | Items   | Specifications    | Quantity in Nos. |
|------|---|-------------------|------------------|
| 1.   | Desktops  | As per Annexure A | 06               |
| 2.   | UPS   | As per Annexure A | 06               |
| 3.   | MFM Printer   | As per Annexure A | 02               |
| 4.   | LED TV 65"  | As per Annexure A | 01               |
| 5.   | Wireless Mic and Camera with Mic for<br>Virtual Meeting | As per Annexure A | 1 set            |
| 6.   | Internet Facility                                       | As per Annexure A |                  |

110C-B

# Annexture - A

| Desktop Sp | ecification |
|------------|-------------|
|------------|-------------|

| Desktop.  | Specification   |
|---|---|
| Items   | Specification   |
| Cabinet Form Factor                                       | Tower/Micro Tower (15.1 to 26 Litres)   |
| Chipset Number  | Intel H670/Intel® H770 or higher Chipset  |
| Processor Make  | Intel   |
| Processor   | x86 64-bit architecture   |
| Processor Generation                                      | 13 Or higher  |
| Processor Description                                     | Intel Core i3 or higher   |
| Processor Number  | Întel Core i3 13100 or higher   |
| Number of Cores and Threads per Processor                 | Max Turbo Frequency 4.5Ghz, Minimum 4 Cores and 8 Threads or higher   |
| Operating System  | Windows 11 Home Factory Preloaded   |
| RAM Size (GB)   | DDR-4 8GB 3200 (16 X1) or higher (2 DIIM Slots)   |
| RAM Expandability up to (using spare DIMM Slots in GB)    | 64 GB or higher   |
| Integrated Graphics                                       | Intel UHD Graphics 770 or higher  |
| Supported for discrete NVIDIA/AMD Graphics Card up to 6GB | Yes   |
| Type of Drives used to populate the Internal Bays         | NVMe SSD  |
| Total HDD Capacity (GB)                                   | NA  |
| Total SSD Capacity (GB)                                   | 512GB NVMe SSD  |
| Optical Drive   | Optional  |
| Drive Bays  | Two 3.5" (2.5") HDD   |
| Slots for Upgradation                                     | 1 PCI Express 4.0 x16,<br>1 PCI Express 3.0 x1,<br>1 PCI (Full Height),<br>2 M.2 slots for WLAN & SSD   |
| LAN   | LAN: Integrated 10/100/1000M  |
| Ports and Connectors                                      | Front: 1 headphone/microphone combo; 3 Super Speed USB SGbps signalling rate; 2 SuperSpeed USB 10 Gbps signalling rate; 1 USB Type-C, total 6nos USB in front for easy access Rear: 1 HDMI; 1 Serial Port; 1 line in; 1 line out; 1 power connector; 1 RJ-45; 1 DP; 2 USB 2.0 |
| Firmware Trusted Platform Module                          | TPM 2.0   |
| Hardware Security lock slot                               | Security lock slot  |
| Power Supply  | 180-260Watt Internal power supply with minimum 90% efficiency   |
|   | Bidder should submit OEM bid specific authorization & the same authorization may be verified by the respective OEM if required.  OEM must have the ISO 9001,14001, ISO 20001, ISO 27001   |
| 12 120 0E   | Certificate   |
| Certification   | Microsoft Windows, Energy star 8.0 certified  |
|   | Bidder should submit BIS, BEE, EPEAT, UL, RoHS Certificate o products at the time of participation of the Bid.  |
| Keyboard Mouse  | USB Keyboard; USB Optical Mouse   |
| Monitor   | 19.5" LED Display with CTO Certified and same must be belongs to the same OEM   |
| Years of Warranty   | 3 Year Onsite Warranty  |

| 600 VA Line Interactive UPS Specifications  SI, No. Feature General Specifications |   |   |  |
|--|---|---|--|
| 31, 190.   | reacure                                 | General Specifications  |  |
| 1  | UPS Capacity (total)                    | 600VA/360W  |  |
| 2  | Input Voltage                           | 230 VAC nominal   |  |
| 3  | Input Frequency                         | 45 - 65 Hz  |  |
| 4  | Brownout Transfer                       | 145 VAC typical   |  |
| 5  | Over-voltage Transfer                   | 290 VAC typical   |  |
| 6  | Voltage on Battery                      | 230 VAC typical (stepped approximated sine wave)  |  |
| 7  | Frequency - On Battery                  | 50Hz typical  |  |
| 8  | Transfer Time                           | @50 Hz : 6 ms typical, 10 ms max  |  |
| 9  | Air Ventifation                         | Should have Side and Back Honey bee Perforation for heat dispersion   |  |
| 10   | Protection from Humidity & Dust         | UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity   |  |
| 11   | Battery Saver Option                    | UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years   |  |
| 12   | No Load Shutdown                        | UPS Should work on loads of 2-3 watts also  |  |
| 13   | AC Surge Protection                     | Full time, 160 joules   |  |
| 14   | Automatic Re start of UPS               | In case the UPS backup is totally drained and automat<br>switched off, when the grid power resumes the UPS Shou<br>Auto Start without human interference. |  |
| 15   | Type (maintenance-free)                 | 12V, 7.2 Ah   |  |
| 16   | Typical recharge time                   | 4-6 hours   |  |
| 17   | Operating Temperature                   | 0°C to 40°C   |  |
| 18   | Storage Temperature                     | -15°C to 45°C   |  |
| 19   | 3 power outlets                         | With battery backup and surge protection  |  |
| 20   | Power Cord                              | 1.2 meters  |  |
| 21   | Runtime for Single PC load (60W ± 15W)  | 27 min (normal mode)  |  |
| 22   | Runtime for Workstation PC (100W ±15W)  | 13 min (normal mode)  |  |
| 23   | Battery Saver (to save on battery life) | Thru toggle button on front panel   |  |
| 24   | Certification                           | BIS   |  |
| 25   | Designed and Manufactured in India      | Yes   |  |
| 26   | Warranty                                | 2 years   |  |

|   | Generic   |
|---|---|
| Description of Stores   | Multifunction Machine Printer with Minimum 1 Year On Site<br>Warranty, including Cartridge and Power Cord/Adapter |
| Core Function   | Print, Scan and Copy  |
| Print Technology  | Laser   |
| Cartridge Technology  | Composite Cartridge   |
| Type of Printing  | Monochrome (Black)  |
| RAM Size (MB)   | 256   |
| Storage Capacity (in GB)  | 0   |
| Features  | Fax   |
| Operating System Compatibility  | Windows 10 and Above, Linux, Mac OS, Windows Server   |
|   | Printing  |
| Print Paper Size  | A4 and Legal  |
| Minimum Print Speed per<br>Minute as per ISO/IEC 24734 in<br>A4 Size-Monochrome (Black)<br>(in PPM) | 26 to 30  |
| Minimum Print Speed per<br>Minute as per ISO/IEC 24734 in<br>A4 Size-Colour (in PPM)                | Not Applicable  |
| Minimum Speed per Minute as<br>per ISO/IEC 24734 in A3 Size-<br>Mono (in PPM)                       | Not Applicable  |
| Minimum Speed per Minute as<br>per ISO/IEC 24734 in A3 Size-<br>Color (in PPM)                      | Not Applicable  |
| Auto Duplexing Printing/Coping (2-sided Feature)  | Yes   |
|   | Scanning  |
| Maximum Scan Area<br>(Platen/Flatbed Size)  | A4 and Legal  |
| A4 Scan Speed -Colour (Image<br>Per Minute) @ 300 x 300 dpi   | 11 to 20  |
| Scan To Functions   | Email   |
| A4 Scan Speed - Mono (Image<br>Per Minute) @ 300 x 300 dpi  | 11 to 20  |
|   | COPYING   |
| Reduction and Enlargement<br>Feature  | Yes   |

| PAPER HANDLING                        |
|---------------------------------------|
|                                       |
| Type Automatic Document Feeders (ADF) |
| ))   reeders (ADF)                    |
|                                       |
| of 31 to 40                           |
| 31 to 40                              |
| 4                                     |
|                                       |
|                                       |
|                                       |
|                                       |
| M 101 to 200                          |
| M                                     |
|                                       |
| No                                    |
| 0                                     |
|                                       |
|                                       |
| USB Port,Ethernet Port,Wi-Fi          |
| USB Cable                             |
| Performance                           |
| 700                                   |
|                                       |
| C:                                    |
| 9.                                    |
|                                       |
|                                       |
|                                       |
| 0                                     |
|                                       |
|                                       |
|                                       |
|                                       |
|                                       |
|                                       |
|                                       |
|                                       |
| 10,001 to 20,000                      |
|                                       |
|                                       |
| POWER                                 |
| Single Phase AC 220 - 240 V 50 CO.    |
| 1300 240 V, 30 - 60 Hz                |
|                                       |
|                                       |
|                                       |
| 10                                    |
| 10                                    |
| 10                                    |
|                                       |
| 30                                    |
|                                       |
|                                       |

| Minimum Operating Humidity (%RH)  | 20                           |
|---|------------------------------|
| Maximum Operating Humidity (%RH)  | 80                           |
|   | Dimension                    |
| Standard Machine Weight with<br>Single Tray (in Kg)   | 11                           |
|   | Certification                |
| BIS CRS Compliance  | Yes as per IS 13252 (Part 1) |
| Maximum Number of Prints covered under Product warranty (Whichever is earlier)  | 30000                        |
| EPR Registration in respect of<br>the manufacturer/authorised<br>importer as per E waste rules<br>as amended up to date | Yes                          |
| Agreed to Provide a copy of EPR Registration Certificate to the Buyer on Demand   | Yes                          |

| Parties and American Pares. |  |   |
|-----------------------------|--|---|
|                             | Screen Size                            | 65  |
|                             | Brightness (cd/m²)                     | 350Nits or better   |
|                             | Contrast Ratio                         | 1200:1  |
| General Features            | Dynamic Contrast Ratio                 | 400,000:1   |
| General reatures            | Response Time (ms)                     | 8.0   |
|                             | Display resolution (H x V, pixels)     | 3840 x 2160   |
|                             | HDR (High Dynamic Range) compatibility | Yes (HDR10, HLG)  |
|                             | Aspect Ratio                           | 16:9  |
|                             | Portrait/Tilt Compatibility            | Yes   |
|                             | Dimming type -                         | Frame Dimming   |
|                             | Display Device                         | LCD   |
|                             | Panel Type                             | IPS   |
|                             | Backlight type                         | Direct LED  |
| Display features            | Color gamut (NTSC)                     | 69%   |
|                             | Operation time                         | 16/7  |
|                             | Haze (%)                               | 1 %   |
|                             | Viewing Angle (Right/Left)             | 178 (89/89) degree  |
|                             | Viewing Angle (Up/Down)                | 178 (89/89) degree  |
|                             | HDMI Signal  Speaker Position          | 4096 x 2160p (24, 50, 60 Hz<br>3840 x 2160p (24, 25, 30, 50<br>60 Hz), 1080p (30, 50, 60 Hz)<br>1080/24p, 1080i (50, 60 Hz),<br>720p (30, 50, 60 Hz),<br>720/24p, 576p, 576i<br>480p,480i |
| Audio Specs                 | Audio Power Output                     | 10W + 10W   |
| Professional                | Pro settings                           | Yes (Simple Pro settings menu   |
| features                    | HDMI auto wake-up                      | Yes   |
|                             | Operating System                       | Android TV  |
|                             | On-board Storage (GB)                  | 16GB  |
|                             | RAM                                    | 3GB   |
| Network Specs               | Wi-Fi Certified                        | Yes   |
| To the special              | Wireless LAN                           | Integrated  |
|                             | USB playback codecs                    | MPEG1:MPEG1/MPEG2 PS:MPEG2/MPEG2 WEBM:AV1/AC4/ogg/AAC   |
| Convenience                 | On Screen Clock                        | Yes   |
| features                    | Sleep Timer                            | Yes   |
|                             | On/Off Timer                           | Yes   |
|                             | Chromecast built-in                    | Yes   |
|                             | Apple AirPlay                          | Yes   |
|                             | IP Control                             | Yes   |
| Control Specs               | RS-232C Control                        | Yes   |
|                             | HDMI-CEC                               | Yes   |
|                             | HDCP                                   | HDCP2.3 (for HDM11/2/3)   |
|                             | Composite Video Input (s)              | 1 (Side, Mini jack)   |

| Inputs and outputs | HDMI inputs total                         | 3 (3Side)                  |  |
|--------------------|---|----------------------------|--|
|                    | Analog Audio Input (s) (Total)            | 1 (Side Analog Conversion) |  |
|                    | Digital Audio Output (s)                  | 1 (Side)                   |  |
|                    | USB ports                                 | 2 (Side)                   |  |
|                    | Ethernet inputs                           | 1 (Side)                   |  |
| Design features    | VESA® Hole Pitch (W x H)                  | 300 x 300 mm               |  |
| Environment Specs  | Rated Power Consumption                   | 226W                       |  |
|                    | Power Consumption (in Standby)            | 0.5 W                      |  |
|                    | Dynamic Backlight Control                 | Yes                        |  |
|                    | Power Saving Mode / Back Light Off Mode   | Yes                        |  |
|                    | Dimension of TV without Stand (W x H x D) | 1462 x 842 x 71 mm         |  |
| Measurements       | Dimension of TV with Stand (W x H x D)    | 1462 x 912 x 338 mm        |  |
|                    | Dimension of Package Carton (W x H x D)   | 1588 x 965 x 184 mm        |  |
|                    | Weight of TV without Stand                | 20.4 kg                    |  |
| Weight             | Weight of TV with Stand                   | 21.3 kg                    |  |
|                    | Weight of Package Carton (Gross)          | 28 kg                      |  |